



VK86

Touchless Surface Mount Exit Button

NO / NC / COM;
Standby blue light, response green light;
Delay time adjustable 0~30s;
Distance adjustable 5~20cm.



VDC 12~24



Contactless



Two Color



Adjustable



Custom Delay



Mechanical Button

Product Standard Features

- Wide Voltage DC 12~24V
- Standby current 30mA, trigger current 60mA
- Mechanical Button for emergency using
- With emergency button function (infrared sensing function is attenuated or malfunctions)
- With buzzer alert (factory default on)

Specification

Model	VK86
Size (mm)	87L*87W*22H
Weight (kg)	0.072
Power Supply	DC12-24V
Output Contact	NO / NC / COM
Material	ABS spray silver body, Alex Panel
Operating Current	Standby 30mA, Trigger 60mA
LED Indicator	Standby blue, Response green
Sensitive Distance	5-20cm
Time Delay	0-30s
Double Insurance Control	Contact-free induction + Mechanical button
Mechanical Life	500,000 Tested aging test qualified
Installation	Exposed (no bottom box required)
Operating Temp	-20°C~55°C (-4~131°F)
Operating Humidity	0-95% (RH)
Package Quantity	1 PCS / box, 100 PCS / case

View	Front (Standy)	Front (Response)
Photos		
View	Side	Back
Photos		

Dimensions

